



## FLAT PANEL TROFFERS

These flat panel LED fixtures reorient the light source to the panel and ensure brightness, providing a skylight-like appearance, smooth distribution, and a powerful value. A white extruded aluminum frame, steel backing, optional battery backup, quality LED driver, and versatile control options make the Flat Panel Troffer Gen 2 a quality, high-efficacy product. At less than 1/2" thick, our flat panels are extremely light and minimal - making them easy to install, and aesthetically pleasing to your current design.

### LONG LIFETIME

- 5 year warranty backed by U.S. company founded in 1949
- Aluminum thermal management ensure LEDs run cool for longer life
- Quality driver resists typical noise and surge in office environments

### BRIGHT SAVINGS

- Typical payback of 6 - 24 months
- Potential for rebate savings through DLC certifications (refer to DLC QPL at [www.designlights.org](http://www.designlights.org))
- 0-10 Dimming standard
- Up to 125 lumens/watt
- Utilize integrated dimming for additional energy savings
- Easily install wired lighting controllers such as our new ETG-CSHOP
- Check [www.designlights.org/](http://www.designlights.org/) for which versions are DesignLights Consortium® (DLC).

### FULL CIRCLE DESIGN

- Output of 3,125 - 7,500 lumens
- Engineered with quality, metal frame
- Units are designed to mount in ceiling grid; optional surface-mount
- Easy installation in tight places like ceilings with shallow plenums and the unit can be replaced in seconds
- Integrated junction box allows easy wiring of AC and dimming

### ILLUMINATING RESULTS

- 80 CRI standard enhances color and clarity
- Potential for rebate saving through DLC certifications (refer to DLC QPL at [www.designlights.org](http://www.designlights.org))
- Smooth, even distribution, spreads light out over entire surface
- Acrylic light pipe diffuser replicates skylight-like appearance
- Typical mounting heights of 8' - 20'

## POSSIBLE APPLICATIONS

- Office space
- Commercial
- Garages
- Retail environments
- Schools
- Inspection lighting

MODEL	CRI	CCT	LUMENS	TOTAL WATTS	LUMENS/WATTS	TEMPERATURE
2x4 Flat Panel	80					-10 to 40°C
ETG-T24-WL850-36W*		5,000K	4,500	36	125	
ETG-T24-WL840-36W*		4,000K	4,500	36	125	
ETG-T24-WL850-60W*		5,000K	7,500	60	125	
ETG-T24-WL840-60W*		4,000K	7,500	60	125	
2x2 Flat Panel						
ETG-T22-WL840-25W*		4,000K	3,125	25	125	
ETG-T22-WL850-36W*		5,000K	4,500	36	125	
ETG-T22-WL840-36W*		4,000K	4,500	36	125	
1x4 Flat Panel						
ETG-T14-WL840-25W*		4,000K	3,125	25	125	
ETG-T14-WL850-36W*		5,000K	4,500	36	125	
ETG-T14-WL840-36W*	4,000K	4,500	36	125		

\*DLC qualified

COMPARE TO		
Existing Fixture	Troffer Replacement	Energy Savings*
4 Tube T12	2x4 36 (similar performance)	<b>\$54.31</b>
	2x4 60 (enhanced performance)	<b>\$43.80</b>
3 Tube T8	2x4 36 (similar performance)	<b>\$26.28</b>
	2x4 60 (enhanced performance)	<b>\$15.77</b>
4 Tube T12 2x2	2x2 36 (enhanced performance)	<b>\$19.27</b>
2 Tube T12 1x4	2x4 36 (enhanced performance)	<b>\$19.27</b>

\*based on 12 hour daily usage, \$0.10 per kwh

#### YOUR PART NUMBER

ETG-T panel size -WL CRI/CCT - wattage - power optional

**24** (2x4)  
**22** (2x2)  
**14** (1x4)

**850** (80 CRI, 5000K)  
**840** (80 CRI, 4000K)

**25** (25W: 2x2, 1x4 only)  
**36** (36W)  
**60** (60W: 2x4 only)

**P14** (battery backup)

## COMPLEMENTARY PRODUCTS

We have several complete lines of products for both indoor, outdoor, and specialty applications (such as grow, inspection, hazardous) to exceed your organization's energy savings goals, fast-track your ROI, and enhance your overall light output. Explore the versatile products below more on our website at [www.HornerLighting.com](http://www.HornerLighting.com) to quick start your savings today.



#### White LED Linear (WLL)

4' or 8' linear configurations, high or low bay applications



#### Square Canopy & Parking

Adjustable output of up to 8,700 lumens, integrated light and motion sensor



#### Mantis Task Light

4' linear configurations, task or low bay applications

#### Flat Panel Accessories

##### ETG-SWI-087

Slide dimmer 0-10 VDC control

##### ETG-T14-SMF

1'x4' Surface Mount Frame

##### ETG-T22-SMF

2'x2' Surface Mount Frame

##### ETG-T24-SMF

2'x4' Surface Mount Frame

##### ETG-CSHOP-2

Wired lighting controller

##### ETG-DIM-SLD-12

Slide dimmer 0-10 VDC, 6' cable