



WHITE LINEAR LED (WLL) SERIES

Our 4ft. and 8ft. White LED Linears are powerful, efficient, and designed for long life and low maintenance. Utilizing the same proven design as our flagship Remote Phosphor LED Linears, we have translated that over into the realm of White LEDs. Perfect for high bay lighting applications in industrial settings, retail, or manufacturing, our White LED Linears are durable, versatile, and powerful. With an extruded aluminum casing, high-quality white LEDs, and a plethora of options and adders, these 4ft and 8ft fixtures are well-suited and customizable for most indoor uses.

LONG LIFETIME

- 5 year warranty backed by U.S. company founded in 1949
- Rated for 62,000 hrs at L90
- Quality driver with integrated 4 kV surge
- -40°C to 50°C ambient temperature ensures long lifetime in a variety of conditions
- Superior LED thermal management ensures long lifetime

ILLUMINATING RESULTS

- 80 CRI standard enhances color and clarity
- Powerful light engine creates even output with 5 different distributions
- Optional field-installable aluminum reflectors for low/high bay, aisle, and task applications
- Clear plexiglass diffuser provides control, minimizing potential for glare
- Typical mounting heights of 8' - 60'
- No horizontal dust collecting surface bulbs

FULL CIRCLE DESIGN

- Output of 9,845 - 77,192 lumens
- Made in USA with global components
- Engineered with quality aluminum and space-age materials
- Minimalist design improves cooling and minimizes shipping costs
- Quickly mount via cable (standard)
- 347/480 VAC option available

BRIGHT SAVINGS

- Typical payback of 12 - 24 months
- Optional 0-10 Dimming
- Up to 169 lumens/watt
- Utilize optional motion and/or daylight sensors for additional energy savings
- Reduce downtime and minimize maintenance costs
- Potential for rebate savings through DLC certifications (refer to DLC QPL at www.designlights.org)

POSSIBLE APPLICATIONS

- | | | |
|---------------------|----------------------|-----------------------------|
| ■ Grocery stores | ■ Stadiums | ■ Hangars |
| ■ Warehouses | ■ Natatoriums | ■ Indoor storage facilities |
| ■ Department stores | ■ Industrial garages | ■ Gymnasiums |

MODEL	WEIGHT	DIMENSIONS	CRI*	CCT*	LUMENS	TOTAL WATTS	LUMENS/WATTS	L90
4 FT LINEAR								
ETG-WLL-1060	3.53 lbs.	49"L x 3.1"W x 3"H	80+	5000K	9,845	60	164.1	62,000 hrs
ETG-WLL-1080*	3.53 lbs.	49"L x 3.1"W x 3"H	80+	5000K	13,127	80	164.1	
ETG-WLL-2120*	7.3 lbs.	49"L x 6.1"W x 3"H	80+	5000K	19,810	120	165.1	
ETG-WLL-2160*	7.3 lbs.	49"L x 6.1"W x 3"H	80+	5000K	26,414	160	165.1	
ETG-WLL-3240*	10.9 lbs.	49"L x 10.6"W x 3"H	80+	5000K	39,628	240	165.1	
ETG-WLL-4320*	14.6 lbs.	49"L x 15.1"W x 3"H	80+	5000K	54,129	320	169.2	
ETG-WLL-6480*	21.8 lbs.	49"L x 24.1"W x 3"H	80+	5000K	77,192	480	160.8	
8 FT LINEAR								
ETG-W8LL-1080	7.5 lbs.	96"L x 3.1"W x 3"H	80+	5000K	13,207	80	165.1	62,000 hrs
ETG-W8LL-1160	7.5 lbs.	96"L x 3.1"W x 3"H	80+	5000K	26,414	160	165.1	
ETG-W8LL-2320	14.8 lbs.	96"L x 6.13"W x 3"H	80+	5000K	54,129	320	169.2	

* These models only - DLC 5.1 certified

• For Power and CRI/CCT - 'P1' and 'C1' will be standard if no other option is selected



YOUR PART NUMBER

length LED modules power CRI/CCT sensors other

ETG-W LL- -P -C - -

leave blank (4')
8 (8')

1060 (1 LED module/60W)
1080 (1 LED module/80W)
2120 (2 LED modules/120W)
2160 (2 LED modules/160W)
3240 (3 LED modules/240W)
4320 (4 LED modules/320W)
6480 (6 LED modules/480W)
1080 (1 LED module/80W)
8' 1160 (1 LED module/60W)
2320 (2 LED modules/320W)

1 (120-277VAC)
with wired 0-10V
dimming driver
2 (480VAC)
4 (120-277VAC)
dimming terminal
block

1 (80 CRI,
5000K)

M1 (on/off
motion sensor)
M2 (on/off motion
sensor cold
storage)
G1 (120VAC
NEMA 5)
G2 (277VAC
NEMA 7
twist lock)

call factory



ETG-AY2T-12
Two non-adjusting toggle mounts,
12" (standard with 1, 2, or 3-Tube Linear)



ETG-AY2T-18
Two non-adjusting toggle mounts, 18"
(standard with 4 or 6-Tube Linear)