



ATLAS PARKING / AREA / FLOOD SERIES

Light up your parking lot, building, surrounding areas (and savings) with the versatile output of the Horner Atlas Series. Ideal in most parking applications, the Atlas Shoebox also excels in perimeter, pathway, general area, and flood projects. The lightweight durable, design, along with a universal mounting bracket, minimizes waste while maximizing efficiency and ROI. With three wattage options, we're sure to find a solution to exceed your organization's requirements and expectations.

LONG LIFETIME

- Premium, top-tier LEDs
- 5 year warranty backed by U.S. company founded in 1949
- Quality driver and 20 kV surge, standard
- Superior LED thermal management
- -40°C to 50°C ambient temperature ensures long lifetime in a variety of conditions

ILLUMINATING RESULTS

- Replaces 250 - 1,000 watt fixtures
- Clean, even distribution
- UV stable polycarbonate lens does not yellow over time
- Typical mounting heights of 15' - 35'

TRIED AND TRUE

- Passed Sweep Vibration Test
- Passed Area Light Salty Spray Test

FULL CIRCLE DESIGN

- Output of 15,000 - 36,000 lumens
- Engineered with cast aluminum magnesium alloy for lightweight, durable housing
- One universal mount that works as a slip fitter, square and round pole mount
- IP65 Dust and Water protection UL wet-rated
- Dual process coating with electrophoresis and TGIC powder coat provides years of environmental/corrosion protection
- Daylight Sensor and Occupancy Sensors optional
- 0-10V Dimming

BRIGHT SAVINGS

- Typical payback of 12 - 24 months
- Up to 150 lumens/watt
- 7-Pin Sensor Receptacle

POSSIBLE APPLICATIONS

- Ideal for parking lots
- Lighting for trails, walkways, & pedestrian paths
- Security and perimeter
- Flood and wall washing
- Highly effective in dealer/retail lots
- Architectural building

MODEL	WEIGHT	DIMENSIONS	CRI	CCT	LUMENS	WATTS	Lm/W	L90	L70	EPA
ETG-SBS100-WL740-P1-L6-03M	11.5 lbs.	17.5" L x 15" W x 3.3" H	>70	4000K	15,000	100	150	>37,000 hrs	>72,000 hrs	1.9 ft ²
ETG-SBS150-WL740-P1-L6-03M	11.5 lbs.				22,500	150				
ETG-SBS240-WL740-P1-L6-03M	13.5 lbs.				36,000	240				

Contact factory for additional 4000K and 5000K options.

MOUNTING OPTIONS AND ACCESSORIES:



Universal Mount
ETG-BKT-SBS-UNV
*Mounts to square or round pole and 2 3/8" slipfitter



Daylight Sensor
ETG-SEN-7P-MV-DIM
*Turns on/off at 100 lux
*Dims to 50% at midnight and brightens to 100% the last hour before sunrise

YOUR PART NUMBER

ETG-SBS wattage -WL7 CCT - power -L6- lens type

100 (100W) 150 (150W) 240 (240W) 40 (4000K) P1*(120-277VAC) 02M*(Type 2 Medium) 03M (Type 3 Medium) 04M* (Type 4 Medium) 05M* (Type 5 Medium)

* Special Order: contact factory for lead times/details

COMPARE TO		
Existing Fixture	Atlas Replacement	Energy Savings**
1,000 W	240 (similar performance)	\$402.96
400 W	150 (similar performance)	\$133.59
100 W	100 (enhanced performance)	\$75.46

*replaces a depreciated light source with similar performance while maximizing energy savings
**based on 12 hour daily usage, \$0.10 per kwh