

MANTIS SERIES TASK LIGHT

The dual linear outputs, lightweight/compact design, and wide output position the Mantis Series of task lights as an efficient added value for your organization. Ideal within low bay, aisle way, and project-driven lighting installations, the Mantis Series features a versatile design: two linear strips of LEDs distribute an even range of light directly below and around the area needing illuminated. The zone where these beams intersect is the most powerful, while still providing enough ambient light around the perimeters of the source to be more than sufficient for general lighting purposes.

LONG LIFETIME

- Premium, top-tier LEDs
- 5 year warranty backed by U.S. company founded in 1949
- L95 > 72,000 hrs
- Life Rating > 50,000+ hrs maintains 92.5% initial output
- -40°C to 50°C ambient temperature ensures long lifetime in a variety of conditions
- No horizontal surface lighting for dust accumulation

FULL CIRCLE DESIGN

- Output of 4,410 - 8,820 lumens
- Engineered with quality, space-age materials
- Unique, dual beam design
- Quickly mount via clips

BRIGHT SAVINGS

- Typical payback of 12 - 24 months
- 0-10 Dimming standard
- Up to 147 lumens/watt
- Utilize optional motion sensor for additional energy savings

ILLUMINATING RESULTS

- 80 CRI standard enhances color and clarity
- Dual surface light output minimizes glare
- Integrated reflectors provide even output
- Standard acrylic diffuser provides control, minimizing potential for glare
- Typical mounting heights of 8' - 14'



POSSIBLE APPLICATIONS

- | | | |
|-----------------------|-------------------------|-------------------------|
| ■ Retail overhead | ■ General inspection | ■ Industrial work zones |
| ■ Automotive showroom | ■ Aisle, path, low bays | ■ Overhead bench areas |

MODEL	WEIGHT	DIMENSIONS	CRI	CCT	LUMENS	WATTS	Lm/W	L95
White LED								
ETG-MT2H-WL850-30W-G1	2 lbs. 6 oz.	3.5"W x 24"L x 2.75"H	80	5000K	4,410	30	147	>72,000mW
ETG-MT4H-WL850-60W-G1	4 lbs.	3.5"W x 47.5"L x 2.75"H	80	5000K	8,820	60	147	>72,000mW

YOUR PART NUMBER

ETG - length - WL850 - - plug - optional motion sensor

MT2H (2')
MT4H (4')

30W (2' only)
60W (4' only)

G1 standard
(6' molded
5-15 120 VAC)

M1 (on/off)
M8 (continuous
dimming with
daylight harvest)



ETG-MT4H-WL850-60W-G1



Surface Mounting Brackets Shown (Optional accessory)
ETG-BKT-B39 - 2 per pack



M1 Sensor
on/off




M8 Sensor
Continuous dimming with
daylight harvest

(discard, not needed for this product)



Chain Kit Shown
(standard)

POSSIBLE APPLICATIONS



Office & Lab Areas



Retail Overhead



Workshop/Bench Areas